

FOR RACING USE ONLY



Installation instructions for A.W.E. Tuning DV1 Diverter Valve

97-05 Audi A4, VW Passat 1.8T

Thank you for purchasing the A.W.E. Tuning DV1 Diverter Valve. With the DV1 Diverter Valve, we believe you have purchased the finest diverter valve for the money. Follow these instructions, and you'll have your new A.W.E. Tuning DV1 Diverter Valve installed quickly and easily.



Parts List

- 1 A.W.E. Tuning DV1 Diverter Valve
- 2 20-32mm hose clamp
- 1 10-16mm hose clamp
- 1 Medium length zip tie


Required Tools:

- Medium flat blade screwdriver
- Tin Snips
- Pliers

Step 1:

Place the front of the vehicle on jackstands and remove the undertray beneath the engine.


The diverter valve (DV) is located on the passenger side, in the area between the passenger front tire and the lower spoiler, just to the passenger side of the AC compressor.



Step 2:

Cut the one time use crimp clamp with tin snips. Loosen screw clamp with a flat head screwdriver. Remove vacuum line from top of valve and remove valve from car.

Installation of A.W.E. Tuning DV1 Diverter Valve is essentially the reverse of removal. Use enclose clamps to attach boost hoses and vacuum line and the enclosed ziptie to attach vacuum hose to boost hose to keep it clear of moving objects.



With the A.W.E. Tuning DV1 Diverter Valve you can enjoy a 1.8T without boost loss and surging that the stock DVs are known for.

Any questions or comments, let us know:

AWE-Tuning.com

1-888-565-2257

sales@awe-tuning.com

Any questions or comments, let us know!

AWE-Tuning.com

1-888-565-2257

Page 2 of 2

Copyright 2008, A.W.E. Tuning. No part of this document may be reused or duplicated without the express permission of A.W.E. Tuning/Secor Ltd. All rights reserved.



AWE Tuning
2385C Maryland Rd
Willow Grove, PA 19090

215.658.1670
www.awe-tuning.com

Thank you for choosing A.W.E. Tuning as your performance automotive parts supplier. Please remember that a performance car is only as strong as its weakest link. Therefore, it is vital that you maintain your vehicle to factory specifications.

By installing or using the purchased product, the Consumer accepts this warranty and any specific Manufacturer warranties enclosed.

Limited Warranty

The following warranty is valid only in the United States.

The Manufacturer's full warranty applies to all products sold.

Secor Ltd. (A.W.E. Tuning) warrants to the original retail purchaser (Consumer) the A.W.E. Tuning DV1 Diverter Valve against defects for 6 months.

Upon verification of warranty coverage, A.W.E. Tuning will repair or replace the defective product at their discretion, without charge. This is the only remedy the Consumer has for any loss or damage, however arising, due to nonconformity in or defect of the product. This warranty does not cover consequential damage, loss of time or revenues, inconvenience, loss of use of vehicle, damage to the vehicle or components, or other incidental or indirect damage.

All warranties are void if the product was not installed by a certified auto mechanic, improperly serviced, modified, or used in a way not intended by the Manufacturer. Use of product in Motorsports or Racing conditions is grounds for warranty denial. Motorsports and Racing is an inherently abusive operational condition, and it is impossible to warranty for this type of usage.

The Consumer is responsible for ensuring that the product is installed in a safe and proper manner, and should cease usage of the product immediately if an unsafe or improper condition is noted. If an unsafe or improper condition is noted, the Consumer should then immediately contact the facility where the product was installed or A.W.E. Tuning directly.

Please contact the original place of purchase for any warranty claims or explanations of this document.